


22801 MAH PLUS-258/4LED/PC

Dust-proof LED tube light fitting 5905339228017

















Kanlux MAH PLUS 4LED are LED equivalents of popular luminaires. Their core asset consists in the fact that they can use T8 LED light sources that are 1200 mm or 1500 mm long. This solution is perfect for industrial use.

GENERAL DATA:

Colour: grey

Place of assembly: ceiling mounted

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m Possibility of fixture-loop-through connection: yes Power supply of T8 LED fluorescent lamps: Unilateral

Length [mm]: 1570 Width [mm]: 125 Height [mm]: 92 Number of clasps: 10

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50

Maximum power [W]: 2 x max 58

Class of protection against electric shock: I

Lampshade material: PC Light source: T8 LED Light source included: no

Cap: G13

Ambient temperature range to which the product can be

exposed: 5÷25

Enclosure material: plastic Handle material: Metal Clasp material: plastic

Connection type: Bolt terminal block

Range of sections of wires used [mm²]: 1÷2,5

IP class: 65

LOGISTIC DATA:

Unit of measurement: unit Packaging method: 6

Number of units in the secondary packaging: 1

Number of units in the packaging: 6

Net unit weight [g]: 2000 Grammage [g]: 2436.67

Length of a unit pack [cm]: 157.5

Date of issue: 01.03.2024, 10:38

We reserve the right to make technical changes. The data contained in this material are not legally binding. Photometry: the results obtained from testing were from a specific sample.





22801 MAH PLUS-258/4LED/PC

Dust-proof LED tube light fitting



Width of a unit pack [cm]: 14 Height of a unit pack [cm]: 6.5


Weight of a cardboard box [kg]: 14.62002 Width of a cardboard box [cm]: 28.5 Height of a cardboard box [cm]: 22 Length of a cardboard box [cm]: 158 Volume of a cardboard box [m³]: 0.099066

ADDITIONAL INFORMATION:

 MAH PLUS 4 LEDs/PC light fixtures are designed for T8 LED 220-240 V~; 50/60 Hz light sources with one-sided power supply


KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ + GLASSv4 / LDC (Polar)


Luminaire: KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ + GLASSv4 Lamps: 2 x T8 LED GLASSv4 24W-NW




KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ + GLASSv3 / LDC (Polar)

Luminaire: KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ + GLASSv3 Lamps: 2 x T8 LED GLASSv3 24W-NW













22801 MAH PLUS-258/4LED/PC

Dust-proof LED tube light fitting



Oprawa: KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ i GLASSv2 Lampy: 2 x T8 LED GLASSv2 24W-NW



KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ i T8 Miledo / Krzywa rozsyłu światła (biegunowo)

Oprawa: KANLUX S.A. (kat 22801) MAH PLUS-258/4LED/ i T8 Miledo Lampy: 2 x T8 LED 22W-NW

