

Kanlux



**Everything under control!
New offer of remote
controls for LED strips**

Kanlux



1 ZONE



Kanlux REMOTE 0 1 MONO/CCT-B

**A small remote control
designed for single-color
and CCT tapes.**

Single-zone

**Allows you to adjust brightness
and color temperature.
Equipped with a magnetic
mount.**

2.4GHz RF radio control.

Range: max 30m.

Battery powered: 3V (1 x CR20232).

Dimensions: Ø 60 mm.

Compatible with the Kanlux CTRL 12/24V MONO/
CCT controller.

Kanlux



1 ZONE



Kanlux REMOTE L 1 MONO/CCT-W

A simple and convenient remote control with a rotary button designed for single-color and CCT strips.

**Single-zone
Allows you to adjust brightness and color temperature. Equipped with a magnetic mount.**

2.4GHz RF radio control. Range: max 30m.

Battery powered: 3V (1 x CR20232).

Dimensions: 86 x 86 mm.

Compatible with the Kanlux CTRL 12/24V MONO/CCT controller.

Kanlux



REMOTE 4 MONO/CCT-B

Universal remote control designed for single-color and CCT strips

Four-zone (individual lighting settings in each zone).

Provides adjustable brightness and color temperature. Equipped with a magnetic mount.

2.4GHz RF radio control.

Range: max 30m

Battery powered: 2 x 1.5V (2 x AAA)

Dimensions: 38 x 140 mm

Compatible with the Kanlux CTRL 12/24V MONO/CCT controller.

Kanlux



REMOTE 4 RGB/CCT-B

A convenient and functional remote control designed for **RGB W and RGB CCT strips**

Four-zone

(individual lighting settings in each zone). **Allows you to control the brightness level, color, and color temperature of the light. Equipped with a magnetic holdery.**

2.4GHz RF radio control. Range: max 30m.

Battery powered: 2 x 1.5V (2 x AAA)

Dimensions: 45 x 140 mm

Compatible with the Kanlux CTRL 12/24V RGBW CCT controller.

Kanlux



REMOTE 8 RGB/CCT-W

Advanced remote control designed for RGB W and RGB CCT strips

Eight-zone (individual lighting settings in each zone).

Allows you to adjust the brightness, color, and color temperature of the light. Allows you to select the lighting mode.

2.4GHz RF radio control. Range: max 30m.
Battery powered: 2 x 1.5V (2 x AAA)
Dimensions: 47 x 153 mm
Compatible with the Kanlux CTRL 12/24V RGBW CCT controller.

Kanlux controllers and remote controls dedicated to operating LED strips and neon lights

			Current [A]	Colour	Voltage [V]	zones	Battery
22147	CTRL 12/24V MONO/CCT	Controller for LED TAPES MONO/ CCT	max 10	WHITE	12 DC; 24 DC		
22144	REMOTE MONO	Remote control		white	2 x 1,5 DC	1	2 x AAA
22145	REMOTE CCT	Remote control		white	2 x 1,5 DC	4	2 x AAA
22136	REMOTE 4 MONO/CCT-B	Remote control		black	2 x 1,5 DC	4	2 x AAA
22138	REMOTE L 1 MONO/CCT-W	Remote control		white	3 DC	1	1 x CR20232
22137	REMOTE O 1 MONO/CCT-B	Remote control		black	3 DC	1	1 x CR20232

			Current [A]	Colour	Voltage [V]	zones	Battery
22148	CTRL 12/24V RGBW CCT	Controller for LED TAPES RGBW/ RGB CCTB	max 10	WHITE	12 DC; 24 DC		
22146	REMOTE RGBW	Remote control		white	2 x 1,5 DC	4	2 x AAA
NEW 22135	REMOTE 4 RGB/CCT-B	Remote control		black	2 x 1,5 DC	4	2 x AAA
22139	REMOTE 8 RGB/CCT-W	Remote control		white	2 x 1,5 DC	8	2 x AAA

Remote control: 2.4GHz RF
Remote control range: max. 30m
Electric shock protection class: III
Material: plastic

**CHECK
FULL
OFFER**

