

# ***Kanlux***



**Surface-mounted luminaires**  
Kanlux **AQILO IP65**

# Kanlux



GU10



E14



E27

## Kanlux AQILO IP65

is the first family of surface-mounted luminaires with such a **high ingress protection rating in the range of Kanlux offer**. It is characterised by simple styling and is available in three colours: white, black and graphite.

<b>33360</b>	AQILO IP65 DSO-W
<b>33361</b>	AQILO IP65 DSO-B
<b>33362</b>	AQILO IP65 DSO-GR
<b>36641</b>	AQILO E14 IP65 DSO-W
<b>36642</b>	AQILO E14 IP65 DSO-B
<b>36640</b>	AQILO E14 IP65 DSO-GR
<b>36644</b>	AQILO E27 IP65 DSO-W
<b>36645</b>	AQILO E27 IP65 DSO-B
<b>36643</b>	AQILO E27 IP65 DSO-GR

GU10

E14

E27



**Kanlux**

## High protection - IP65

the luminaire is designed for use in rooms where electrical devices are exposed to increased humidity and the risk of flooding, such **as bathrooms, kitchens, cellars, and for use in outdoor areas of the house** (terraces, balconies, covered entrances to the house, etc.).

# Kanlux



## Kanlux **AQILO E14 & E27**

**The AQILO E14 IP65 and AQILO E27 IP65 models use a reflector to direct the light output from the light sources downwards instead of onto the inner surface of the luminaire** (the reflector eliminates light absorption by the luminaire body).

As a result, in the luminaires, it is possible to use light sources with lower wattage and luminous efficacy without the risk of lighting the room too dimly.

**Kanlux**



# Kanlux

## Technical parameters:

**Power supply:** 220-240 VAC

**Cap:** GU10, E14, E27

**Power:** GU10-max 7W, E14-max 10W, E27-max 20W

**Lampshade material:** stop aluminium


**Materiał klosza:** tworzywo sztuczne

**Colour:** biały, czarny, szary (antracyt)


**Protection class:** I

**Ingress protection:** IP 65


**Ambient temperature range to which the product can be exposed:** -20÷35°C



AQILO GU10



AQILO E14



AQILO E27

# Kanlux

## Kanlux AQILO IP65



**Well-packed**