

Kanlux



EAN: 5905339221513

Controller for LED tapes
Kanlux 22151 CTRL 12-48V ALL-IN



12V
24V
48V



Date of issue: 08.07.2026, 14:35

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com


EN

PRODUCT PARAMETERS

Rated voltage [V]	12 DC; 24 DC; 48 DC
Rated current [A]	max 20
IP class	20
Control	RF 2,4GHz
Range [m]	max 30
Standard support	DIM, MONO, CCT, RGB, RGBW, RGB+CCT
Type	Controller for LED tapes

DIMENSIONS AND MOUNTING

Height [mm]	23
Width [mm]	47
Length [mm]	119
Connection type	Terminal block



MATERIAL AND CONSTRUCTION

Colour	white
Material	plastic
Class of protection against electric shock	III

LOGISTICS

Unit of measurement	unit
Packaging method	200
Number of units in the secondary packaging	1
Number of units in the packaging	200
Net unit weight [g]	76
Grammage [g]	107.5
Gross unit weight [g]	100
Length of a unit pack [cm]	12
Width of a unit pack [cm]	3.5
Height of a unit pack [cm]	5
Weight of a cardboard box [kg]	21.5
Width of a cardboard box [cm]	35.5
Height of a cardboard box [cm]	26
Length of a cardboard box [cm]	51.5
Volume of a cardboard box [m ³]	0.047535

Date of issue: 08.07.2026, 14:35

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com