

25481 BORD XS DLP-50-BE

Ceiling-mounted spotlight fitting
5905339254818



PRODUCT PARAMETERS	
Rated voltage [V]	220-240 AC
Rated frequency [Hz]	50
Maximum power [W]	max 10
Cap (Light source)	GU10
Light source	PARI6 LED
Place of application	Indoors
IP class	20
The fixture is movable vertically [°]	25
Lighting-fixture angle regulation	in one axis
Lighting-fixture angle regulation [°]	25

DIMENSIONS AND MOUNTING	
Height [mm]	115
Diameter [mm]	80
Place of assembly	ceiling mounted
Connection type	Bolt terminal block

DIMENSIONS AND MOUNTING

Range of sections of wires used [mm ²]	1÷2,5
--	-------

LOGISTICS

Unit of measurement	unit
Packaging method	20
Number of units in the secondary packaging	1
Number of units in the packaging	20
Net unit weight [g]	248
Grammage [g]	308,5
Gross unit weight [g]	250

LOGISTICS

Length of a unit pack [cm]	9
Width of a unit pack [cm]	9
Height of a unit pack [cm]	12,5
Weight of a cardboard box [kg]	6,17
Width of a cardboard box [cm]	20
Height of a cardboard box [cm]	27
Length of a cardboard box [cm]	47
Volume of a cardboard box [m ³]	0.02538

MATERIAL AND CONSTRUCTION

Colour	beige
Enclosure material	aluminum alloy
Class of protection against electric shock	I
Shape	round
Minimum distance from the illuminated object	0,5m
Ambient temperature range to which the product can be exposed	5÷25

Date of issue: 07.10.2026, 13:42

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com