

Ceiling-mounted LED light fitting




Kanlux PORTOS LED is a facade luminaire. Thanks to it, you can illuminate the facade and highlight the property number. Kanlux PORTOS LED in its universal form perfectly fits any surface. Perfectly smooth walls add character, and on facades such as brick, cladding board or structural plaster, it emphasizes the shape and brings out their uniqueness. Kanlux PORTOS LED is a durable and resistant to external factors luminaire that can be used both indoors and outdoors, without fear that moisture and dust will reduce its work efficiency. The Kanlux PORTOS LED SE version of the luminaire has a built-in dusk sensor.

GENERAL DATA:

Colour: white
Place of assembly: wall mounted
Place of application: Indoors and outdoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Replaceable light source: no
Length [mm]: 262
Width [mm]: 166
Height [mm]: 51
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 5
Class of protection against electric shock: II
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 450
Colour temperature: white
Colour temperature [K]: 4000
Colour uniformity [SDCM]: ≤6
Colour-rendering index Ra: ≥80
Service life [h]: 30000
Number of on/off cycles: ≥15000
Lighting angle [°]: 120
Luminous efficiency of the lamp [lm/W]: 90
Ambient temperature range to which the product can be exposed: -10÷35
Enclosure material: plastic
Sensor type: dusk
Connection type: Self-clamping block



29071 PORTOS LED SE

Ceiling-mounted LED light fitting

Range of sections of wires used [mm²]: 0,5÷1,5

The fixture set includes built-in LED's with the following

energy classes: A++,A+,A

Lamp-heating time [s]: ≤1

Lamp-ignition time [s]: ≤0,5

IP class: 54

Oprawa uruchamia się automatycznie po zapadnięciu

zmroku: <20lx (+/-10lx)

ADDITIONAL INFORMATION:

- Fixtures turns on automatically after dark.

