29345 AL 11W-840-RST-W-NT

Linear LED luminaire



GENERAL DATA:

Colour: white
Place of assembly: ceiling mounted
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Replaceable light source: no
Fixture lighting direction: down
Length [mm]: 573
Width [mm]: 58
Height [mm]: 65
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 11
Class of protection against electric shock: I
Lampshade material: plastic
Diode type: LED SMD
Luminous flux [lm]: 1050
Colour temperature: white
Colour temperature [K]: 4000
Colour uniformity [SDCM]: ≤6
Colour-rendering index Ra: ≥80
Service life [h]: 50000
Luminous-flux-retention factor at the end of rated service life: L80B10
Number of on/off cycles: ≥30000
Lighting angle [°]: X85/Y85
Luminous efficiency of the lamp [lm/W]: 95
Ambient temperature range to which the product can be exposed: 5÷25
Shade type: louvre
Enclosure material: aluminum alloy
Connection type: Self-clamping block
Range of sections of wires used [mm²]: 1,5÷2,5
The fixture set includes built-in LED's with the following energy classes: A++,A+,A
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5
IP class: 20

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website

Date of issue: 08.09.2020, 12:03
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

29345 AL 11W-840-RST-W-NT

Linear LED luminaire





ACCESSORIES:

32540 ALIN CORD 1F-W

Power supply terminal for ALIN luminaires and tracks, 1-phase, white, 150 cm

32541 ALIN CORD 1F-B

Power supply terminal for ALIN luminaires and tracks, 1-phase, black, 150 cm

Date of issue: 08.09.2020, 12:03

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN

29345 AL 11W-840-RST-W-NT

Linear LED luminaire

32542 ALIN CORD 1F-SR

Power supply terminal for ALIN luminaires and tracks, 1-phase, silver 150 cm

07871 ROPE-NT 150 SINGLE

ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set

29557 ALIN NT GRIP

Wall bracket for the ALIN luminaire, 2 pcs included

27109 KLOSZ MPR AL 11W/17W

MPR shade for fitting ALIN, MPR SHADE AL 11W/17W,(27109)

We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.

EN