



LED light source



STANDARD A60



Kanlux XLED combines the best features of traditional bulbs and modern LED light sources. Therefore, we talk about it as the first real "LED bulb". A70 glass bulb has extraordinary size in the shape of a traditional bulb and LED diodes are arranged inside in such a way so that light can part in all directions.

GENERAL DATA:

Lamp designed for decorative lighting: Not applicable

Compatible with a dimmer: no

Height [mm]: 126

Diameter [mm]: 70

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC

Rated frequency [Hz]: 50

Lamp-power factor: 0.5

Rated power [W]: 15

Lampshade material: glass

Light source: A70

Diode type: LED FILAMENT

Total rated luminous flux [lm]: 2450

Colour temperature: Warm white

Colour temperature [K]: 2700

Colour uniformity [SDCM]: ≤6

Colour-rendering index Ra: ≥80

Rated lamp-service life [h]: 10000

Number of on/off cycles: ≥15000

Rated beam angle [°]: 320

Rated light level [°]: 320

Light source EEL: A++

Lamp rated current [mA]: 110

Annual power consumption [kWh/1000h]: 15

Luminous efficiency of the lamp [lm/W]: 163

Ignition time [s]: ≤0,5

Lamp-heating time to 60% of the full luminous flux [s]:
Negligible

Lamp-heating time to 95% [s]: <2

Lamp premature-failure indicator: <5% po 1000h

Lamp service life factor after the period of 6000h [%]:
≥90

Luminous flux retention factor at the end of rated service life [%]: ≥70

Luminous flux retention factor after the period of 6000h [%]: ≥80

Declaration of equality in power rating [W]: 150

LED light source

| **Light source shape:** standardowa