


Rail-mounted projector



Kanlux ACORD ATL 1 are integrated lighting fixtures to be mounted on three-phase track. These are lamps that can be adapted to our individual needs. We can choose white or black, two powers (18W and 30W), light color and lighting angle (standard is 60°, but we can replace the reflector and change the angle to 15° or 36°) depending on whether we want to illuminate the surface or a specific detail. Kanlux ACORD ATL 1 stands for 50 000 hours of durability and a 5-year warranty. Branded key components (LED COB and power supply), high level of real color rendering (CRI > 90) and elimination of glare (UGR < 19) are other advantages of these unique luminaires.

GENERAL DATA:

Colour: black
Place of assembly: rail TEAR
Place of application: Indoors
Minimum distance from the illuminated object: 0,5m
Compatible with a dimmer: no
Replaceable light source: no
Integrated LED light source: yes

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC
Rated frequency [Hz]: 50
Maximum power [W]: 30
Class of protection against electric shock: II
Diode type: LED COB
Luminous flux [lm]: 2850
Colour temperature: Warm white
Colour temperature [K]: 3000
Colour uniformity [SDCM]: ≤6
Colour-rendering index Ra: ≥90
Service life [h]: 50000
Number of on/off cycles: ≥30000
Lighting angle [°]: 60
Luminous efficiency of the lamp [lm/W]: 95
Ambient temperature range to which the product can be exposed: 5÷25
Enclosure material: aluminum alloy
Protective glass material: plastic
The fixture set includes built-in LED's with the following energy classes: A++,A+,A
Lamp-heating time [s]: ≤1
Lamp-ignition time [s]: ≤0,5

33135 ATL1 30W-930-S6-B

Rail-mounted projector



The fixture is movable horizontally [°]: 315

The fixture is movable vertically [°]: 90

IP class: 20

ADDITIONAL INFORMATION:

- 5 years Warranty under the terms of the warranty statement, available on our website
- for installation on the TEAR N busbar

ACCESSORIES:

33140 REF ATL1-18W-S15 Reflector for the ATL 1 luminaire, 18 W, 15 degrees



33141 REF ATL1-18W-S36 Reflector for the ATL 1 luminaire, 18 W, 36 degrees



33142 REF ATL1-30W-S15 Reflector for the ATL 1 luminaire, 30 W, 15 degrees



33143 REF ATL1-30W-S36 Reflector for the ATL 1 luminaire, 30 W, 36 degrees

