

07172 BERG DL-100

In-ground lighting fitting


















Kanlux BERG is a durable ground-recessed luminaire using a replaceable light source with an GU10 screw. It works great in illumination of driveways, alleys, sidewalks etc. It is manufactured of best quality materials owing to which can resist pressure up to 2 tons.

GENERAL DATA:

Colour: stainless steel

Place of assembly: mounted on the ground, in-ground

Place of application: Indoors and outdoors

Minimum distance from the illuminated object: 0,5m **Possibility of fixture-loop-through connection**: yes

Replaceable light source: yes Light source included: no Fixture lighting direction: Top

Height [mm]: 145 Diameter [mm]: 113 Number of chokes: 2

TECHNICAL DATA:

Rated voltage [V]: 220-240 AC Rated frequency [Hz]: 50 Maximum power [W]: max 10

Class of protection against electric shock: |

Light source: PAR16 LED

Cap: GU10

Ambient temperature range to which the product can be

exposed: -20÷35

The fixture is adapted to the light sources of the

following energy classes: A++,A+,A,B,C,D,E

Enclosure material: steel

Panel/frame material: stainless steel
Protective glass material: Tempered glass
Connection type: Belt terminal black

Connection type: Bolt terminal block

Range of sections of wires used [mm 2]: $1 \div 2,5$

Permissible static pressure [kN]: 20

IK class: 08 IP class: 67





07172 BERG DL-100

In-ground lighting fitting



