

KDB-series distribution board





KDB-S06T

		E B	П	7	ΙP
			L iii	<u> </u>	
KDB-S06T	23610	white / blue	6P	wall mounted	30
KDB-S08T	23611	white / blue	8P	wall mounted	30
KDB-S12T	23612	white / blue	12P	wall mounted	30
KDB-S18T	23613	white / blue	18P	wall mounted	30
KDB-S24T	23614	white / blue	24P	wall mounted	30
KDB-S36T	23615	white / blue	36P	wall mounted	30
KDB-F06T	23616	white / blue	6P	Recessed mount in the wall	30
KDB-F08T	23617	white / blue	8P	Recessed mount in the wall	30
KDB-F12T	23618	white / blue	12P	Recessed mount in the wall	30
KDB-F18T	23619	white / blue	18P	Recessed mount in the wall	30
KDB-F24T	23620	white / blue	24P	Recessed mount in the wall	30
KDB-F36T	23621	white / blue	36P	Recessed mount in the wall	30
KDB-F12P	23622	white	12P	Recessed mount in the wall	30
KDB-F24P	23623	white	24P	Recessed mount in the wall	30
KDB-S12P	23624	white	12P	wall mounted	30
KDB-S24P	23625	white	24P	wall mounted	30
KDB-F54P	28340	white	54P	Recessed mount in the wall	30
KDB-F54P-M	28341	white	18P	Recessed mount in the wall	30

KDB series switchboards meeting the requirement for heat resistance at the temperature of 650°C, can be used on non-flammable surfaces only (e.g. full solid walls made of non-combustible materials). They cannot be used on





KDB-series distribution board

flammable surfaces (e.g. plasterboard, wood boards, etc.), on the so-called "hollow walls" or on technical sections

• Material: plastic





KDB-series distribution board












KDB-F54P























294 109 KDB-S24T










KDB-series distribution board











KDB-F12T


KDB-F18T


KDB-F24T

KDB-F36T











KDB-F12P

KDB-F24P

KDB-S12P

KDB-S24P





KDB-F54P

KDB-F54P-M