

FUTURIO LED DALI 55W 1480mm

Прахохерметично осветително тяло LED



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm] 0,5+2,5	0,5m	CE	EAC	PZH	UK CA	



FTD1500 55W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	lm/W	[mm]	°C	
FTD1500 55W-840-OPL	28658	55	4000	опалов	X130/Y110	7500	136	1480	-25÷35
FTD1500 55W-840-RYF	28666	55	4000	grooved	X115/Y105	8150	148	1480	-25÷35
FTD1500 55W-840-INT	28668	55	4000	призматичен, с тесен лъч	X70/Y95	7900	144	1480	-25÷35
FTD1500 55W-840-ASY	28669	55	4000	призматичен, асиметричен	X75/Y95	7900	144	1480	-25÷35

- 5-годишна Гаранция при спазване на гаранционните условия, достъпни в уебсайта
- Материал на корпуса: PC
- Материал на дифузера: PC



FTD1500 55W-840-OPL



FTD1500 55W-840-RYF




FTD1500 55W-840-INT




FTD1500 55W-840-ASY

FUTURIO LED DALI 55W 1480mm


Прахохерметично осветително тяло LED




FTD1500 55W-840-OPL



FTD1500 55W-840-RYF



FTD1500 55W-840-INT



FTD1500 55W-840-ASY