

HIERRO

линейно LED осветително тяло










 [V] 220-240 AC	 [Hz] 50	 ≥ 30000	 [h] 50000	 + ellipse $\leq 6x$ MacAdam	 Ra 80	 SMD
		 IP 20		 [°C] 5÷25		
 [mm ²] 1,5÷2,5		 0,5m				



HR-LL-WW-W-PT

HIERRO

линейно LED осветително тяло

								
HR-LL-WW-W-PT	37029	23	3000	растер	X60/Y60	бял	3000	875
HR-LM-WW-W-PT	37030	32	3000	растер	X60/Y60	бял	4000	875
HR-LH-WW-W-PT	37031	42	3000	растер	X60/Y60	бял	4950	875
HR-LL-WW-B-PT	37037	23	3000	растер	X60/Y60	черен	2650	875
HR-LM-WW-B-PT	37038	32	3000	растер	X60/Y60	черен	3550	875
HR-LH-WW-B-PT	37039	42	3000	растер	X60/Y60	черен	4350	875
HR-LL-WN-W-PT	37045	23	3500	растер	X60/Y60	бял	3050	875
HR-LM-WN-W-PT	37046	32	3500	растер	X60/Y60	бял	4100	875
HR-LH-WN-W-PT	37047	42	3500	растер	X60/Y60	бял	5050	875
HR-LL-WN-B-PT	37053	23	3500	растер	X60/Y60	черен	2700	875
HR-LM-WN-B-PT	37054	32	3500	растер	X60/Y60	черен	3650	875
HR-LH-WN-B-PT	37055	42	3500	растер	X60/Y60	черен	4500	875
HR-LL-NW-W-PT	37061	23	4000	растер	X60/Y60	бял	3150	875
HR-LM-NW-W-PT	37062	32	4000	растер	X60/Y60	бял	4200	875
HR-LH-NW-W-PT	37063	42	4000	растер	X60/Y60	бял	5150	875
HR-LL-NW-B-PT	37069	23	4000	растер	X60/Y60	черен	2800	875
HR-LM-NW-B-PT	37070	32	4000	растер	X60/Y60	черен	3750	875
HR-LH-NW-B-PT	37071	42	4000	растер	X60/Y60	черен	4600	875

- Материал на корпуса: стомана, пластмаса
- Материал на дифузера: пластмаса



HIERRO

линейно LED осветително тяло



HR-LL-WW-W-PT



HR-LM-WW-W-PT



HR-LH-WW-W-PT



HR-LL-WW-B-PT



HR-LM-WW-B-PT



HR-LH-WW-B-PT



HR-LL-WN-W-PT



HR-LM-WN-W-PT



HR-LH-WN-W-PT



HR-LL-WN-B-PT



HR-LM-WN-B-PT



HR-LH-WN-B-PT



HR-LL-NW-W-PT



HR-LM-NW-W-PT



HR-LH-NW-W-PT



HR-LL-NW-B-PT

HIERRO


линейно LED осветително тяло



HR-LM-NW-B-PT



HR-LH-NW-B-PT



HR-L-PT

