

## HIERRO

линейно LED осветително тяло



 [V] 220-240 AC	 [Hz] 50	 $\geq 30000$	 [h] 50000	 ellipse $\leq 6x$ MacAdam	 Ra 80	 SMD
		 IP 20		 [°C] 5÷25		
 [mm <sup>2</sup> ] 1,5÷2,5		 0,5m				



HR-ML-WW-W-PT

## HIERRO

линейно LED осветително тяло



Model	W	Tc [K]	TYPE	L°	lm	[mm]
HR-ML-WW-W-PT <b>37026</b>	18	3000	растер	X60/Y60	бял	2350 595
HR-MM-WW-W-PT <b>37027</b>	23	3000	растер	X60/Y60	бял	2850 595
HR-MH-WW-W-PT <b>37028</b>	28	3000	растер	X60/Y60	бял	3300 595
HR-ML-WW-B-PT <b>37034</b>	18	3000	растер	X60/Y60	черен	2100 595
HR-MM-WW-B-PT <b>37035</b>	23	3000	растер	X60/Y60	черен	2500 595
HR-MH-WW-B-PT <b>37036</b>	28	3000	растер	X60/Y60	черен	2900 595
HR-ML-WN-W-PT <b>37042</b>	18	3500	растер	X60/Y60	бял	2400 595
HR-MM-WN-W-PT <b>37043</b>	23	3500	растер	X60/Y60	бял	2900 595
HR-MH-WN-W-PT <b>37044</b>	28	3500	растер	X60/Y60	бял	3350 595
HR-ML-WN-B-PT <b>37050</b>	18	3500	растер	X60/Y60	черен	2150 595
HR-MM-WN-B-PT <b>37051</b>	23	3500	растер	X60/Y60	черен	2600 595
HR-MH-WN-B-PT <b>37052</b>	28	3500	растер	X60/Y60	черен	3000 595
HR-ML-NW-W-PT <b>37058</b>	18	4000	растер	X60/Y60	бял	2450 595
HR-MM-NW-W-PT <b>37059</b>	23	4000	растер	X60/Y60	бял	3000 595
HR-MH-NW-W-PT <b>37060</b>	28	4000	растер	X60/Y60	бял	3450 595
HR-ML-NW-B-PT <b>37066</b>	18	4000	растер	X60/Y60	черен	2200 595
HR-MM-NW-B-PT <b>37067</b>	23	4000	растер	X60/Y60	черен	2650 595
HR-MH-NW-B-PT <b>37068</b>	28	4000	растер	X60/Y60	черен	3050 595

- Материал на корпуса: стомана, пластмаса
- Материал на дифузера: пластмаса



## HIERRO

линейно LED осветително тяло



HR-ML-WW-W-PT



HR-MM-WW-W-PT



HR-MH-WW-W-PT



HR-ML-WW-B-PT



HR-MM-WW-B-PT



HR-MH-WW-B-PT



HR-ML-WN-W-PT



HR-MM-WN-W-PT



HR-MH-WN-W-PT



HR-ML-WN-B-PT



HR-MM-WN-B-PT



HR-MH-WN-B-PT



HR-ML-NW-W-PT



HR-MM-NW-W-PT



HR-MH-NW-W-PT



HR-ML-NW-B-PT

## HIERRO


линейно LED осветително тяло



HR-MM-NW-B-PT



HR-MH-NW-B-PT



HR-M-PT

