

## KIENO DALI LED P3

Офис LED осветително тяло за скрит монтаж



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 80	SMD
DALI		IP 20		[°C] 5÷25		
[mm²] 0,5÷2,5	[m] 0,5m	CE	UK CA			



KND-L6D-NW-B-P3



	[°]	[mm]	Tc [K]	TYPE	[°]		
KND-L6D-NW-B-P3	<b>37531</b>	26	3850	4000	soczewka	60	черен
KND-L6D-NW-W-P3	<b>37519</b>	26	4400	4000	soczewka	60	бял
KND-L6D-WW-B-P3	<b>37525</b>	26	3650	3000	soczewka	60	черен
KND-L6D-WW-W-P3	<b>37513</b>	26	4150	3000	soczewka	60	бял
KND-L9D-NW-B-P3	<b>37534</b>	26	3750	4000	soczewka	90	черен
KND-L9D-NW-W-P3	<b>37522</b>	25	3750	4000	soczewka	90	бял
KND-L9D-WW-B-P3	<b>37528</b>	26	3600	3000	soczewka	90	черен
KND-L9D-WW-W-P3	<b>37516</b>	26	4050	3000	soczewka	90	бял

- Материал на корпуса: метал
- Материал на дифузера: пластмаса

## KIENO DALI LED P3


Офис LED осветително тяло за скрит монтаж



KND-B-P3



KND-W-P3



KND-P3

