

## DABA N LED SMD

Stropní LED svítidlo



[V] 220-240 AC	[Hz] 50	[°] 120	≥20000	[h] 40000	ellipse ≤ 6x MacAdam	Ra 80
Hg	SMD			IP 66		[°C] -15÷35
IK 10	[mm] 0,75-2,5	[m] max 8	[°] H360	[s]-[min] 10-10		
[lx] 5/15/50/2000	[m] 0,5m	CE	EAC	PZH	UK CA	



DABA N LED SMD DL-16W



	[W]	[lm]	Tc [K]		SENSOR	
DABA N LED SMD DL-16W	<b>19062</b>	16	1300	4000	bílá	mikrovlnný
DABA N LED SMD DL-22W	<b>19063</b>	22	1900	4000	bílá	mikrovlnný

Energeticky úsporné svítidlo Kanlux DABA N umožňuje snížit náklady na energii díky použití snímačů pohybu a soumraku. To způsobí, že svítí, pouze když je to nutné. Kromě toho jeho parametry (IP66, IK10) znamenají, že může být namontován prakticky kdekoli! Funkce STAND BY DIMMING znamená, že po naprogramovaném čase bez pohybu přejde plafon do pohotovostního režimu a snižuje světelný tok o 20%.

- Materiál korpusu: PC
- Materiál difuzoru: PC

## DABA N LED SMD


Stropní LED svítidlo




DABA N LED SMD DL-16W



DABA N LED SMD DL-22W



DABA N LED SMD DL-16W



DABA N LED SMD DL-22W