

Kanlux

Kanlux CTRL 12/24V RGBW CCT



IP
20



CTRL 12/24V RGBW CCT



In [A]



CTRL 12/24V RGBW CCT	22148	12 DC; 24 DC	max 10	max 30		
REMOTE RGBW	22146	bílá	2 x 1,5 DC	2 x AAA	max 30	4
REMOTE 8 RGBW/CCT-W	22139	bílá	2 x 1,5 DC	2 x AAA	max 30	8
REMOTE 4 RGBW/CCT-B	22135	černá	2 x 1,5 DC	2 x AAA	max 30	4
REMOTE N 8 RGBW/CCT-W	22134				max 30	



CTRL 12/24V RGBW CCT




REMOTE RGBW




REMOTE 8 RGBW/CCT-W




REMOTE 4 RGBW/CCT-B




CTRL 12/24V RGBW CCT




REMOTE RGBW



REMOTE 8 RGBW/CCT-W



REMOTE 4 RGBW/CCT-B



REMOTE N 8 RGBW/CCT-
W

Dokument vytvořen: 29.09.2025, 17:55

Změna technický parametrů vyhrazena. Informace uvedené v tomto dokumentu nejsou právně závazné.

Fotometrie: výsledky získané během testování konkrétního exempláře.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

