

SIGO LED

Světelný zdroj LED



[V] 220-240 AC	[Hz] 50	SMD	360° Φ _{use}	ellipse ≤ 6x MacAdam	Ra 80	≥15000
15000 [h]	Hg	Pb	CE	EAC	UK CA	↓



SIGO R39 LED E14



	PON [W]	[W]	[lm] Φ _{use}	Tc [K]	[°]		
SIGO R39 LED E14-WW 22733	4	29	320	3000	120	E14	G
SIGO R39 LED E14-NW 22734	4	29	320	4000	120	E14	G
SIGO R50 LED E14-WW 22735	6	41	490	3000	120	E14	G
SIGO R50 LED E14-NW 22736	6	41	490	4000	120	E14	G
SIGO R63 LED E27-WW 22737	8	54	720	3000	120	E27	F
SIGO R63 LED E27-NW 22738	8	54	720	4000	120	E27	F

Kanlux SIGO LED není pouze úspora energie, ale také životnost 25krát vyšší než u tradičních reflektorových žárovek. Protože jejich tvar i rozměr připomíná standardní reflektorové žárovky, lze je snadno vyměnit bez jakýchkoliv dalších úprav.

- Materiál difuzoru: plast

SIGO LED

Světelný zdroj LED




SIGO R39 LED E14




SIGO R50 LED E14




SIGO R63 LED E27



SIGO R39 LED E14



SIGO R50 LED E14



SIGO R63 LED E27