

KMB6

Jistič, 2P



[Hz]

50

C

2P

2

IP

20

(mm²)

1÷25

°C

-5÷40

TH 35

Ui [V]

500

CE

EAC

VDE

CCC

KMB6-C16/2

	[V]		In [A]
KMB6-C16/2	23178	230/400 AC 2	16
KMB6-C2/2	32556	230/400 AC 2	2
KMB6-C6/2	32583	230/400 AC 2	6
KMB6-C10/2	32584	230/400 AC 2	10
KMB6-C20/2	32586	230/400 AC 2	20
KMB6-C25/2	32587	230/400 AC 2	25
KMB6-C32/2	32588	230/400 AC 2	32
KMB6-C40/2	32589	230/400 AC 2	40
KMB6-C50/2	32590	230/400 AC 2	50
KMB6-C63/2	32591	230/400 AC 2	63

5 let záruky shodně s podmínkami záručního prohlášení dostupného na [internetové stránce](#)

Jistič slouží k ochraně před přetížením a zkratem v instalacích a zařízeních.

• -

KMB6

Jistič, 2P



KMB6-C16/2



KMB6-C2/2



KMB6-C6/2



KMB6-C10/2



KMB6-C20/2



KMB6-C25/2



KMB6-C32/2



KMB6-C40/2




KMB6-C50/2




KMB6-C63/2

KMB6


Jistič, 2P




KMB6-C16/2




KMB6-C2/2




KMB6-C6/2




KMB6-C10/2




KMB6-C20/2




KMB6-C25/2




KMB6-C32/2



KMB6-C40/2



KMB6-C50/2



KMB6-C63/2