

KRD6-2

Proudový chránič, 2P

[Hz]

50

°C

-25÷40

IP

20

2P

2

TH 35

Ui [V]

400

CE

EAC

VDE

UK
CA



KRD6-2/25/30

	[V]	In [A]	IΔn [mA]	Typ proudového chrániče		
KRD6-2/25/30	23180	230 AC 25	30	AC		2
KRD6-2/40/30	23181	230 AC 40	30	AC		2
KRD6-2/63/30	23182	230 AC 63	30	AC		2
KRD6-2/16/10	23186	230 AC 16	10	AC		2
KRD6-2/25/100	23187	230 AC 25	100	AC		2
KRD6-2/25/30-A	23188	230 AC 25	30	A		2
KRD6-2/40/30-A	23189	230 AC 40	30	A		2
KRD6-2/16/10-A	23194	230 AC 16	10	A		2
KRD6-2/25/300	23195	230 AC 25	300	AC		2
KRD6-2/40/100	23203	230 AC 40	100	AC		2
KRD6-2/63/100	23204	230 AC 63	100	AC		2
KRD6-2/25/100-A	23225	230 AC 25	100	A		2
KRD6-2/40/100-A	23226	230 AC 40	100	A		2

5 let záruky shodně s podmínkami záručního prohlášení dostupného na [internetové stránce](#)

Proudový chránič: slouží k dodatečné ochraně před úrazem elektrickým proudem, určen pro provoz v sinusových

KRD6-2

Proudový chránič, 2P

střídavých (typ AC) a sinusových střídavých a pulzních proudových obvodech s stejnosměrnou složkou (typ A).



KRD6-2/25/30



KRD6-2/40/30



KRD6-2/63/30



KRD6-2/16/10



KRD6-2/25/100



KRD6-2/25/30-A



KRD6-2/40/30-A



KRD6-2/16/10-A



KRD6-2/25/300



KRD6-2/40/100



KRD6-2/63/100




KRD6-2/25/100-A

KRD6-2


Proudový chránič, 2P




KRD6-2/40/100-A




KRD6-2/25/30




KRD6-2/40/30




KRD6-2/63/30




KRD6-2/16/10




KRD6-2/25/100



KRD6-2/25/30-A




KRD6-2/40/30-A




KRD6-2/16/10-A

KRD6-2


Proudový chránič, 2P




KRD6-2/25/300




KRD6-2/40/100



KRD6-2/63/100



KRD6-2/25/100-A



KRD6-2/40/100-A