

ROUNDA V2LED

Svítidlo typu downlight



 [V] 220-240 AC	 [Hz] 50	 ≥20000	 15000	 ellipse ≤ 6x Macadam	 Ra 80	 SMD
 IP 44/20	 5+25	 °C 5+25	 0,5m	 CE	 EAC	 UKCA
 [mm] 0,05	 [mm] 0,75	 360° Φuse				



	 [W]	 [°]	 [lm]	 Tc [K]
ROUNDA V2LED24W-NW-SN	27220	24	saténový nikl	1700
ROUNDA V2LED6W-NW-SN	27221	6	saténový nikl	300
ROUNDA V2LED12W-NW-SR	28930	12	stříbrná	660
ROUNDA V2LED12W-NW-W	28931	12	bílá	780
ROUNDA V2LED12W-WW-W	28932	12	bílá	720
ROUNDA V2LED18W-NW-SR	28933	18	stříbrná	1080
ROUNDA V2LED18W-NW-W	28934	18	bílá	1260
ROUNDA V2LED18W-WW-W	28935	18	bílá	1200
ROUNDA V2LED24W-NW-W	28936	24	bílá	1680
ROUNDA V2LED6W-NW-W	28937	6	bílá	330
ROUNDA V2LED6W-WW-W	28938	6	bílá	300
ROUNDA V2LED24W-WW-W	33524	24	bílá	1560
ROUNDA V2LED6W-WW-B	33562	6	černá	270

Kanlux ROUNDA V2LED je nová verze populárních kulatých downlightů pro vnitřní použití. Tyto downlighty kombinují estetický design se světlem získaným díky LED technologii. Vysoký stupeň krytí IP44 zabraňuje pronikání vody a prachu do svítidla.

- Materiál korpusu: hliníková slitina
- Materiál difuzoru: plast

ROUND A V2LED

Svítlidlo typu downlight



ROUND A V2LED24W-NW-SN



ROUND A V2LED6W-NW-SN



ROUND A V2LED12W-NW-SR



ROUND A V2LED12W-NW-W



ROUND A V2LED12W-WW-W

ROUNDA V2LED

Svítidlo typu downlight



ROUNDA V2LED18W-NW-SR



ROUNDA V2LED18W-NW-W



ROUNDA V2LED18W-WW-W



ROUNDA V2LED24W-NW-W



ROUNDA V2LED6W-NW-W




ROUNDA V2LED6W-WW-W




ROUNDA V2LED24W-WW-W




ROUNDA V2LED6W-WW-B




ROUNDA V2LED12W



ROUNDA V2LED18W



ROUNDA V2LED24W



ROUNDA V2LED6W