

KMB6

Jistič, 2P



[Hz]

50

B

2P

2

IP

20

(mm²)

1÷25

°C

-5÷40

TH 35

Ui [V]

500

CE

EAC

VDE

CCC

KMB6-B6/2

	[V]		In [A]
KMB6-B6/2	32574	230/400 AC	2 6
KMB6-B10/2	32575	230/400 AC	2 10
KMB6-B16/2	32576	230/400 AC	2 16
KMB6-B20/2	32577	230/400 AC	2 20
KMB6-B25/2	32578	230/400 AC	2 25
KMB6-B32/2	32579	230/400 AC	2 32
KMB6-B40/2	32580	230/400 AC	2 40
KMB6-B50/2	32581	230/400 AC	2 50
KMB6-B63/2	32582	230/400 AC	2 63

5 let záruky shodně s podmínkami záručního prohlášení dostupného na [internetové stránce](#)

Jistič slouží k ochraně před přetížením a zkratem v instalacích a zařízeních.

KMB6

Jistič, 2P



KMB6-B6/2



KMB6-B10/2



KMB6-B16/2



KMB6-B20/2



KMB6-B25/2



KMB6-B32/2



KMB6-B40/2




KMB6-B50/2




KMB6-B63/2

KMB6


Jistič, 2P




KMB6-B6/2




KMB6-B10/2




KMB6-B16/2




KMB6-B20/2




KMB6-B25/2




KMB6-B32/2



KMB6-B40/2



KMB6-B50/2



KMB6-B63/2