

## XLED A60 B22 M

Světelný zdroj LED



|                   |            |          |                          |                         |          |        |
|-------------------|------------|----------|--------------------------|-------------------------|----------|--------|
| [V]<br>220-240 AC | [Hz]<br>50 | FILAMENT | 360°<br>Φ <sub>use</sub> | ellipse<br>≤ 6x MacAdam | Ra<br>80 | ≥15000 |
|                   |            | CE       | EAC                      | UK<br>CA                |          |        |



XLED A60 B22 7W-WW-M



|                       | P <sub>ON</sub> [W] | [W] | [°] | [lm] Φ <sub>use</sub> | Tc [K] | [h] | E <sub>i</sub> A G |
|-----------------------|---------------------|-----|-----|-----------------------|--------|-----|--------------------|
| XLED A60 B22 7W-WW-M  | <b>33102</b>        | 7   | 60  | 810                   | 2700   | 320 | B22 15000 E        |
| XLED A60 B22 7W-CW-M  | <b>33103</b>        | 7   | 60  | 810                   | 6500   | 320 | B22 15000 E        |
| XLED A60 B22 10W-WW-M | <b>33108</b>        | 10  | 99  | 1520                  | 2700   | 320 | B22 10000 D        |
| XLED A60 B22 10W-CW-M | <b>33109</b>        | 10  | 99  | 1520                  | 6500   | 320 | B22 10000 D        |

Kanlux XLED A60 B22 M spojuje ty nejlepší vlastnosti tradičních žárovek a moderních LED zdrojů světla. Matná baňka ve tvaru tradiční žárovky a LED diody uspořádané tak, aby se světlo šířilo všemi směry a úhel svícení byl až 320 stupňů! Žárovky XLED A60 B22 M mají patici B22.

- Materiál difuzoru: sklo


## XLED A60 B22 M

---

Světelný zdroj LED



XLED A60M B22 7W, 10W



XLED A60 B22