

KATRO V2LED

Svítidlo typu downlight

IP
44/20

EA
SY
instal
lation

[V] 220-240 AC	[Hz] 50	≥20000	15000	ellipse ≤ 6x MacAdam	Ra 80	SMD
		IP 44/20		°C 5+25		
[mm] 0,05	[mm] 0,75	0,5m	360° Φ _{use}			



KATRO V2LED 18W-NW-SN

	[W]			[lm]	[°]	T _c [K]
KATRO V2LED 18W-NW-SN	27215	18	saténový nikl	1250	110	4000
KATRO V2LED 24W-NW-SN	27216	24	saténový nikl	1700	110	4000
KATRO V2LED 6W-NW-SN	27217	6	saténový nikl	300	110	4000
KATRO V2LED 12W-NW-SR	28939	12	stříbrná	660	110	4000
KATRO V2LED 12W-NW-W	28940	12	bílá	780	110	4000
KATRO V2LED 12W-WW-W	28941	12	bílá	720	110	3000
KATRO V2LED 18W-NW-SR	28942	18	stříbrná	1080	110	4000
KATRO V2LED 18W-NW-W	28943	18	bílá	1260	110	4000
KATRO V2LED 18W-WW-W	28944	18	bílá	1200	110	3000
KATRO V2LED 24W-NW-W	28945	24	bílá	1680	110	4000
KATRO V2LED 6W-NW-W	28946	6	bílá	330	110	4000

Kanlux KATRO V2LED je nová verze svítidel KATRO N LED, populárních hranatých stropních svítidel pro vnitřní použití. Kombinují estetický design se světlem získaným díky LED technologii. Vysoký stupeň krytí IP44 zabraňuje pronikání vody a prachu do svítidla.

- Materiál korpusu: hliníková slitina
- Materiál difuzoru: plast

KATRO V2LED

Svítilno typu downlight



KATRO V2LED 18W-NW-SN



KATRO V2LED 24W-NW-SN



KATRO V2LED 12W-NW-SR



KATRO V2LED 12W-NW-W



KATRO V2LED 12W-WW-W



KATRO V2LED 18W-NW-SR



KATRO V2LED 18W-NW-W



KATRO V2LED 18W-WW-W

KATRO V2LED


Svítidlo typu downlight




KATRO V2LED 24W-NW-W




KATRO V2LED 6W-NW-W




KATRO V2LED 6W



KATRO V2LED 12W



KATRO V2LED 18W



KATRO V2LED 24W