

Kanlux

Kanlux ALIN IP55 LED



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 55		[°C] -20÷35		
[mm²] 0,5÷1	[m] 0,5m	CE	EAC	UK CA		



AL55-SL-NW-MAT-W-NT



AL55-SL-NW-MAT-W-NT	38979	9,1935	1300	4000	matná	X85/Y95	bílá
AL55-SL-WW-MAT-W-NT	38982	9,1935	1200	3000	matná	X85/Y95	bílá
AL55-SL-NW-MAT-B-NT	38985	9,1935	1300	4000	matná	X85/Y95	černá
AL55-SL-WW-MAT-B-NT	38988	9,1935	1300	3000	matná	X85/Y95	černá



AL55-SL-NW-MAT-W-NT




AL55-SL-WW-MAT-W-NT



AL55-SL-NW-MAT-B-NT



AL55-SL-WW-MAT-B-NT



Dokument vytvořen: 01.10.2025, 14:20

Změna technický parametrů vyhrazena. Informace uvedené v tomto dokumentu nejsou právně závazné.

Fotometrie: výsledky získané během testování konkrétního exempláře.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

