

Downlight



[V] 220-240 AC	[Hz] 50	≥ 20000	15000	ellipse $\leq 60^\circ$ MacAdam	Ra 80	SMD
IP 44/20	House	$5+25$	$5+25$	Arrow	Wiring	
[mm] 0,05	[mm] 0,75	0,5m	360° Φ_{use}	CE	EAC	UK CA



KATRO V2LED 12W-NW-SN

	[W]	[W]	[lm]	[°]	Tc [K]	
KATRO V2LED 12W-NW-SN	27214	12	Nickel satiniert	780	110	4000
KATRO V2LED 18W-NW-SN	27215	18	Nickel satiniert	1250	110	4000
KATRO V2LED 24W-NW-SN	27216	24	Nickel satiniert	1700	110	4000
KATRO V2LED 6W-NW-SN	27217	6	Nickel satiniert	300	110	4000
KATRO V2LED 12W-NW-SR	28939	12	silber	660	110	4000
KATRO V2LED 12W-NW-W	28940	12	weiß	780	110	4000
KATRO V2LED 12W-WW-W	28941	12	weiß	720	110	3000
KATRO V2LED 18W-NW-SR	28942	18	silber	1080	110	4000
KATRO V2LED 18W-NW-W	28943	18	weiß	1260	110	4000
KATRO V2LED 18W-WW-W	28944	18	weiß	1200	110	3000
KATRO V2LED 24W-NW-W	28945	24	weiß	1680	110	4000
KATRO V2LED 6W-NW-W	28946	6	weiß	330	110	4000
KATRO V2LED 6W-WW-W	28947	6	weiß	300	110	3000
KATRO V2LED 24W-WW-W	33529	24	weiß	1560	110	3000
KATRO V2LED 6W-WW-B	33564	6	schwarz	270	110	3000

Kanlux KATRO V2LED ist eine neue Version der KATRO N LED-Leuchten - der beliebten quadratischen Downlights für den Innenbereich. Sie verbinden ästhetisches Design mit LED-Technik. Die hohe Schutzart IP44 verhindert das Eindringen von Wasser und Staub in die Leuchte.

- Gehäusematerial: Aluminiumlegierung

KATRO V2LED

Downlight

- Abdeckungsmaterial: Kunststoff



KATRO V2LED 12W-NW-SN



KATRO V2LED 18W-NW-SN



KATRO V2LED 24W-NW-SN



KATRO V2LED 12W-NW-SR



KATRO V2LED 12W-NW-W



KATRO V2LED 12W-WW-W



KATRO V2LED 18W-NW-SR



KATRO V2LED 18W-NW-W

KATRO V2LED

Downlight



KATRO V2LED 18W-WW-W



KATRO V2LED 24W-NW-W



KATRO V2LED 6W-NW-W




KATRO V2LED 6W-WW-W




KATRO V2LED 24W-WW-W




KATRO V2LED 6W-WW-B




KATRO V2LED 6W



KATRO V2LED 12W



KATRO V2LED 18W



KATRO V2LED 24W