

LED-Aufputz-Büroleuchte



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
	IP 20		5+25			
[mm²] 1,5+2,5	0,5m					



OS 40W-840-MPRM-B-N1

	[W]	[lm]	Tc [K]	TYPE	[°]	
OS 40W-840-MPRM-B-N1	32824	40	4200	4000	mikroprismatisch vom Typ m	X95/Y95 schwarz
OS 40W-840-MPRM-B-N3	32825	40	4300	4000	mikroprismatisch vom Typ m	X90/Y95 schwarz
OS 40W-840-MPRM-W-N1	32820	40	4500	4000	mikroprismatisch vom Typ m	X95/Y95 weiß
OS 40W-840-MPRM-W-N3	32821	40	4400	4000	mikroprismatisch vom Typ m	X90/Y95 weiß

- 5 Jahre Garantie gemäß den Bedingungen der Garantieerklärung, die auf der Website verfügbar ist
- Gehäusematerial: Metall
- Abdeckungsmaterial: Kunststoff



OS 40W-840-MPRM-B-N1




OS 40W-840-MPRM-B-N3




OS 40W-840-MPRM-W-N1




OS 40W-840-MPRM-W-N3




OS 40W-840-MPRM-B-N1



OS 40W-840-MPRM-B-N3



OS 40W-840-MPRM-W-N1



OS 40W-840-MPRM-W-N3