



Kanlux FLUXY LED IP44

- Ladegerät nicht im Lieferumfang enthalten (5V DC)

**IP
44** **DIMM
ING**
function



[V] 3,7 DC 18650 ACCU	[W] ≥15000	[h] 25000	[Ra] 80	[SMD]	DIMM ING function
[III] IP 44	[House] [Down] [Off]	[D---m] 0,1m	[lm/ W] max 82		
CE	EAC	UK CA			



FLUXY LED IP44 W



FLUXY LED IP44 W	37310	max 1,7	max 140	3000	weiß
FLUXY LED IP44 B	37311	max 1,7	max 140	3000	schwarz
FLUXY LED IP44 BL	37312	max 1,7	max 140	3000	blau
FLUXY LED IP44 GN	37313	max 1,7	max 140	3000	grün
FLUXY LED IP44 Y	37314	max 1,7	max 140	3000	gelb



FLUXY LED IP44 W



FLUXY LED IP44 B



FLUXY LED IP44 BL



FLUXY LED IP44 GN



FLUXY LED IP44 Y



FLUXY LED IP44

Erstellt am: 20.11.2024, 11:43

Technische Änderungen vorbehalten. Die in diesem Material enthaltenen Daten sind nicht rechtsverbindlich.
Photometrie: Ergebnisse aus der Untersuchung einer bestimmten Probe.

DE