

# Kanlux



## Kanlux REKA LED

The main advantage of Kanlux REKA LED is a visually unique light effect, which we create ourselves after switching on. Thanks to the wings placed at the bottom and top of the luminaire, we can decide on the direction and width of the luminous flux. The Kanlux REKA lamp shines in two directions - up and down - and the luminous flux can be set independently of each other, creating, for example, a perfectly thin line of light at the top, and at the bottom by setting wide light cascades that will flow from the lamp to the ground. Kanlux REKA LED can be used to illuminate the facades of buildings, terraces, balconies or gazebos' external walls.




- Beam-angle adjustment
- 5 years Warranty under the terms of the warranty statement, available on our website
- Protective glass material: Tempered glass



IP  
54



 220-240 AC	 50	 max 90	 ≥20000	 30000	 ellipse ≤ 6x MacAdam	 80
 COB	 1	 IP 54	 0,5m	 -15÷35	 -15÷35	
 CE	 EAC	 UK CA				





REKA LED EL 7W-L-GR	<a href="#">28990</a>	7	max 360	4000	wall mounted	graphite	up and down
REKA LED EL 7W-O-GR	<a href="#">28991</a>	7	max 380	4000	wall mounted	graphite	up and down
REKA LED EL 7W-L-W	<a href="#">28992</a>	7	max 500	4000	wall mounted	white	up and down
REKA LED EL 7W-O-W	<a href="#">28993</a>	7	max 510	4000	wall mounted	white	up and down



REKA LED EL 7W-L-GR




REKA LED EL 7W-O-GR




REKA LED EL 7W-L-W



REKA LED EL 7W-O-W



REKA LED EL 7W-L



REKA LED EL 7W-O

Date of issue: 22.09.2025, 09:00

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)