

# Kanlux

## Kanlux SANI IP44

KANLUX SANI IP44 are surface holders. They are characterized by simple stylistics and availability in two colours - white and black. High tightness of the holders (IP44) allows using them in rooms where electric devices are exposed to increased humidity and risk of flooding with water e.g. bathroom and kitchen.


- Luminaire only for LED source.

**IP  
44**



SANI IP44 DSO-B

|                |        |              |              |          |              |  |
|----------------|--------|--------------|--------------|----------|--------------|--|
| <br>220-240 AC | <br>50 | <br>PAR16    | <br>GU10     |          | <br>IP<br>44 |  |
| <br>5÷25       |        | <br>0.75÷1.5 | <br>0.75÷1.5 | <br>0,5m |              |  |
|                |        |              |              |          |              |  |





|                  |                       |        |              |
|------------------|-----------------------|--------|--------------|
| SANI IP44 DSO-B  | <a href="#">29240</a> | max 10 | black        |
| SANI IP44 DSO-W  | <a href="#">29241</a> | max 10 | white        |
| SANI IP44 DSO-SN | <a href="#">29242</a> | max 10 | nickel satin |




SANI IP44 DSO-B



SANI IP44 DSO-W



SANI IP44 DSO-SN



SANI IP44 DSO

Date of issue: 20.05.2025, 08:30

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)