

Kanlux



Kanlux TONIL II LED

Kanlux TONIL LED II is a modest in form model with an integrated light source. Its flexible, rubber arm allows you to direct the lighting in the desired direction. At the same time, we can give it the desired shape.

- 3 years Warranty under the terms of the warranty statement, available on our website


FLEXIBLE
arm



[V] 220-240 AC	[Hz] 50	[°] 30	[°] ≥15000	[h] 20000	[°C] ≤6x MacAdam Ellipse	[Ra] 80
[SMD]	[IP] 20	[IP] 20	[IP] 20	[IP] 20	[°C] 5-25	[W] 44
[°] 360	[°] 360	[°] 360	[mm] 0,5-1,5	[m] 0,2m	[W] 0,6W	[lm] 44
[Hg]	CE	EAC	UK CA	WEEE		



TONIL II LED W/G



TONIL II LED W/G	32518	3.3	white / gold	145	3000
TONIL II LED B/G	32519	3.3	black/gold	145	3000
TONIL II LED B	32522	3.3	black	145	3000
TONIL II LED W	32523	3.3	white	145	3000




TONIL II LED W/G




TONIL II LED B/G




TONIL II LED B



TONIL II LED W



TONIL II LED B, B-G, W-G



TONIL II LED W

Date of issue: 23.01.2026, 13:56

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN