

OFIS S

Surface-mounted LED office fixture



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 20		°C 5+25		
[mm²] 1.5+2.5	0,5m					



OS 40W-840-MPRM-B-N1

	[W]	[lm]	Tc [K]	TYPE	[°]	
OS 40W-840-MPRM-B-N1	32824	40	4200	4000	m-type microprismatic	X95/Y95 black
OS 40W-840-MPRM-B-N3	32825	40	4300	4000	m-type microprismatic	X90/Y95 black
OS 40W-840-MPRM-W-N1	32820	40	4500	4000	m-type microprismatic	X95/Y95 white
OS 40W-840-MPRM-W-N3	32821	40	4400	4000	m-type microprismatic	X90/Y95 white

- 5 years Warranty under the terms of the warranty statement, available on our website
- Enclosure material: Metal
- Lampshade material: plastic

OFIS S

Surface-mounted LED office fixture



OS 40W-840-MPRM-B-N1




OS 40W-840-MPRM-B-N3




OS 40W-840-MPRM-W-N1




OS 40W-840-MPRM-W-N3




OS 40W-840-MPRM-B-N1



OS 40W-840-MPRM-B-N3



OS 40W-840-MPRM-W-N1



OS 40W-840-MPRM-W-N3