



BENO LED

Ceiling-mounted LED light fitting



[V] 220-240 AC	[Hz] 50	[°] 110	≥20000	(h) 20000	ellipse ≤ 6x MacAdam	Ra 80
SMD	IP 54	-15 ÷ 35 [°C]	IP 54	-15 ÷ 35 [°C]		
	[mm] 0.5 ÷ 1.5	0,5m	360° Φ _{use}			



BENO 24W NW-O-W

		[W]	[lm]	T _c [K]		SENSOR
BENO 24W NW-O-W	33340	24	2060	4000	white	
BENO 24W NW-O-GR	33341	24	1920	4000	graphite	
BENO 24W NW-L-W	33342	24	2060	4000	white	
BENO 24W NW-L-GR	33343	24	1920	4000	graphite	
BENO 24W NW-O-SE W	33344	24	2060	4000	white	microwave
BENO 24W NW-O-SE GR	33345	24	1920	4000	graphite	microwave
BENO 24W NW-L-SE W	33346	24	2060	4000	white	microwave
BENO 24W NW-L-SE GR	33347	24	1920	4000	graphite	microwave
BENO 24W WW-L-GR	33384	24	1880	3000	graphite	
BENO 24W WW-L-W	33385	24	2040	3000	white	
BENO 24W WW-O-GR	33386	24	1880	3000	graphite	
BENO 24W WW-O-W	33387	24	2040	3000	white	

Kanlux BENO luminaries that's unique design and unique light effect. They were created on the basis of individual order of Kanlux, and their designs were registered by us at the patent office. Kanlux BENO LED also provides high weather resistance (IP54), quick and easy installation on the ceiling or wall, and Beno is equipped with the adjustable movement sensor. Kanlux BENO LED is a multifunctional fitting, which due to its design and its technical aspects, we can apply practically anywhere.

- Enclosure material: plastic
- Lampshade material: plastic

BENO LED

Ceiling-mounted LED light fitting



BENO 24W NW-O-W



BENO 24W NW-O-GR



BENO 24W NW-L-W



BENO 24W NW-L-GR



BENO 24W NW-O-SE W



BENO 24W NW-O-SE GR



BENO 24W NW-L-SE W



BENO 24W NW-L-SE GR

BENO LED

Ceiling-mounted LED light fitting



BENO 24W WW-L-GR




BENO 24W WW-L-W




BENO 24W WW-O-GR



BENO 24W WW-O-W



BENO 24W O



BENO 24W L