

## BTL LED

### Track light projector



<b>[V]</b> 220-240 AC	<b>[Hz]</b> 50	$\geq 30000$	<b>50000</b>	ellipse $\leq 6x$ MacAdam	<b>Ra 90</b>	<b>COB</b>
		<b>IP 20</b>		$5+25$		<b>340</b>
<b>90</b>	<b>0,5m</b>	<b>CE</b>	<b>EAC</b>	<b>UK CA</b>		



BTL 18W-930-W



Model	Power [W]	Flux [lm]	Tc [K]	Beam angle	Beam spread	Color
BTL 18W-930-W	<b>35650</b>	18	1800	3000	15-45	white
BTL 18W-930-B	<b>35651</b>	18	1750	3000	15-45	black
BTL 18W-940-W	<b>35652</b>	18	1800	4000	15-45	white
BTL 18W-940-B	<b>35653</b>	18	1750	4000	15-45	black
BTL 28W-930-W	<b>35654</b>	28	3000	3000	15-45	white
BTL 28W-930-B	<b>35655</b>	28	2800	3000	15-45	black
BTL 28W-940-W	<b>35656</b>	28	3000	4000	15-45	white
BTL 28W-940-B	<b>35657</b>	28	2800	4000	15-45	black
BTL 38W-930-W	<b>35658</b>	38	4000	3000	15-45	white
BTL 38W-930-B	<b>35659</b>	38	3800	3000	15-45	black
BTL 38W-940-W	<b>35660</b>	38	4000	4000	15-45	white
BTL 38W-940-B	<b>35661</b>	38	3800	4000	15-45	black

Kanlux BTL LED is a new design of luminaires adapted to the Kanlux TEAR system and to the majority of 3-circuit rail systems. Luminaires are equipped with a power supply integrated with the adapter. Kanlux BTL are luminaires in the directional version with a lens and lighting angle adjustment in the range from 15° to 45°. Optionally, a diffuser with a honeycomb structure that reduces glare can be used. In Kanlux BTL we can choose the power (18W 28W 38W), the color of the housing (white or black) and the color of light (warm or neutral). The Kanlux BTL series of luminaires has a high color rendering index Ra 90+, and their high quality is confirmed by a 5-year warranty.

## BTL LED

### Track light projector

- 5 years Warranty under the terms of the warranty statement, available on our website
- Enclosure material: aluminum alloy



BTL 18W-930-W



BTL 18W-930-B



BTL 18W-940-W



BTL 18W-940-B



BTL 28W-930-W



BTL 28W-930-B



BTL 28W-940-W



BTL 28W-940-B

## BTL LED

### Track light projector



BTL 38W-930-W




BTL 38W-930-B




BTL 38W-940-W




BTL 38W-940-B



BTL 18W



BTL 28W



BTL 38W