

OFIS S

Recessed - Mounted LED Office Fixture



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 20		°C 5+25		
[mm²] 1.5+2.5	0,5m					



OS 40W-840-MPRM-B-P1

	[W]	[lm]	Tc [K]	TYPE	[°]	
OS 40W-840-MPRM-B-P1	32826	40	4300	4000	m-type microprismatic	X95/Y95 black
OS 40W-840-MPRM-B-P3	32827	40	4400	4000	m-type microprismatic	X90/Y95 black
OS 40W-840-MPRM-W-P1	32822	40	4600	4000	m-type microprismatic	X95/Y95 white
OS 40W-840-MPRM-W-P3	32823	40	4500	4000	m-type microprismatic	X90/Y95 white

- 5 years Warranty under the terms of the warranty statement, available on our website
- Enclosure material: Metal
- Lampshade material: plastic

OFIS S

Recessed - Mounted LED Office Fixture



OS 40W-840-MPRM-B-P1




OS 40W-840-MPRM-B-P3




OS 40W-840-MPRM-W-P1




OS 40W-840-MPRM-W-P3




OS 40W-840-MPRM-B-P1



OS 40W-840-MPRM-B-P3



OS 40W-840-MPRM-W-P1



OS 40W-840-MPRM-W-P3