

XLED EX A60

Źródło światła LED



| | | | | | | |
|----------------------|---------------|----------|--------------------------|-------------------------|----------|--------|
| [V] 220-240 AC | [Hz] 50 | FILAMENT | 360° Φ _{use} | ellipse ≤ 6x MacAdam | Ra 80 | ≥50000 |
| 50000 ^[h] | Hg | | CE | EAC | UK CA | |



XLED EX A60 4W-WW



| | P _{on} [W] | lm/W | (lm) Φ _{use} | T _c [K] | ° | Filament | Ei |
|-------------------|---------------------|------|-----------------------|--------------------|------|----------|-------|
| XLED EX A60 4W-WW | 36243 | 4 | 62 | 840 | 2700 | 320 | E27 A |
| XLED EX A60 4W-NW | 36244 | 4 | 62 | 840 | 4000 | 320 | E27 A |

The next edition of EXTREMELY efficient light sources Kanlux XLED EX A60. The above-average luminous efficiency of 210 lumens per watt makes these LED bulbs 15 times more efficient than their traditional, standard predecessors. 5-year warranty, 50,000 hours of durability, 50,000 on/off cycles are their other advantages. In addition, they have a glass bulb and filament "rods" that resemble tungsten bulbs, but use the latest achievements of LED technology.


- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Materiał klosza: szkło

XLED EX A60

Źródło światła LED



XLED EX A60



XLED EX A60