

HIERRO

Linear LED luminaire



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 80	SMD
		IP 20		[°C] 5÷25		
[mm²] 1.5÷2.5		0,5m				



HR-SL-WW-W-NT

	[W]	Tc [K]		[°]		[m]	[mm]	
HR-SL-WW-W-NT	36940	9	3000	louvre / white	X60/Y60	white	1150	290
HR-SH-WW-W-NT	36941	14	3000	louvre / white	X60/Y60	white	1650	290
HR-SL-WW-B-NT	36948	9	3000	louvre / black	X60/Y60	black	1050	290
HR-SH-WW-B-NT	36949	14	3000	louvre / black	X60/Y60	black	1450	290
HR-SL-WN-W-NT	36956	9	3500	louvre / white	X60/Y60	white	1200	290
HR-SH-WN-W-NT	36957	14	3500	louvre / white	X60/Y60	white	1700	290
HR-SL-WN-B-NT	36964	9	3500	louvre / black	X60/Y60	black	1050	290
HR-SH-WN-B-NT	36965	14	3500	louvre / black	X60/Y60	black	1500	290
HR-SL-NW-W-NT	36972	9	4000	louvre / white	X60/Y60	white	1250	290
HR-SH-NW-W-NT	36973	14	4000	louvre / white	X60/Y60	white	1700	290
HR-SL-NW-B-NT	36980	9	4000	louvre / black	X60/Y60	black	1100	290
HR-SH-NW-B-NT	36981	14	4000	louvre / black	X60/Y60	black	1550	290

HIERRO is a family of fixtures produced at the Kanlux Factory. The minimalist and elegant form fits into the latest trends in architectural design. The stylish solution is widely used in modern offices, shops, and loft spaces as basic, complementary or accent lighting. The great advantages of HIERRO luminaires are: variety of available control and installation methods, low

Date of issue: 19.02.2024, 17:29

We reserve the right to make technical changes. The data contained in this material are not legally binding.

HIERRO

Linear LED luminaire

UGR coefficient, high luminous efficiency, ability to adapt to specific lighting projects and 5-year warranty. This allows you to create energy-saving and modern lighting systems that provide attractive lighting effects.

- Enclosure material: steel, plastic
- Lampshade material: plastic



HR-SL-WW-W-NT



HR-SH-WW-W-NT



HR-SL-WW-B-NT



HR-SH-WW-B-NT



HR-SL-WN-W-NT



HR-SH-WN-W-NT



HR-SL-WN-B-NT



HR-SH-WN-B-NT

HIERRO

Linear LED luminaire



HR-SL-NW-W-NT




HR-SH-NW-W-NT



HR-SL-NW-B-NT



HR-SH-NW-B-NT



HR-SH-NT

