

KIENO DALI LED P3

Recessed - Mounted LED Office Fixture



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 80	SMD
DALI		IP 20		[°C] 5÷25		
[mm²] 0.5÷2.5	0,5m	CE	UK CA			



KND-M6D-NW-B-P3



	[W]	[lm]	T _c [K]	TYPE	[°]	
KND-M6D-NW-B-P3	37532	36	5250	4000	soczewka	60 black
KND-M6D-NW-W-P3	37520	36	6000	4000	soczewka	60 white
KND-M6D-WW-B-P3	37526	36	4950	3000	soczewka	60 black
KND-M6D-WW-W-P3	37514	36	5650	3000	soczewka	60 white
KND-M9D-NW-B-P3	37535	36	5100	4000	soczewka	90 black
KND-M9D-NW-W-P3	37523	35	5100	4000	soczewka	90 white
KND-M9D-WW-B-P3	37529	36	4900	3000	soczewka	90 black
KND-M9D-WW-W-P3	37517	36	5500	3000	soczewka	90 white

- Enclosure material: Metal
- Lampshade material: plastic

KIENO DALI LED P3


Recessed - Mounted LED Office Fixture



KND-B-P3



KND-W-P3



KND-P3

