

Kanlux



Kanlux LTL-E LED

- 5 years Warranty under the terms of the warranty statement, available on our website




[V] 220-240 AC	[Hz] 50	≥ 25000	[h] 50000	$\leq 6^\circ$ MacAdam	Ra 80	SMD
		IP 20		[°C] 5+25		0,5m



LTL-E 15W-60-CCT-W




		[W]	[lm]	T _c [K]	[°]	
LTL-E 15W-60-CCT-W	38396	15	1650(WW)/1800(NW)/1800(CW)	3000/4000/6500	X130/Y105	white
LTL-E 15W-60-CCT-B	38397	15	1350(WW)/1500(NW)/1500(CW)	3000/4000/6500	X130/Y105	black
LTL-E 24W-120-CCT-W	38398	24	2640(WW)/2880(NW)/2880(CW)	3000/4000/6500	X130/Y105	white
LTL-E 24W-120-CCT-B	38399	24	2160(WW)/2400(NW)/2400(CW)	3000/4000/6500	X130/Y105	black



LTL-E 15W-60-CCT-W




LTL-E 15W-60-CCT-B




LTL-E 24W-120-CCT-W




LTL-E 24W-120-CCT-B




LTL-E 15W-60-CCT-W



LTL-E 15W-60-CCT-B



LTL-E 24W-120-CCT-W



LTL-E 24W-120-CCT-B

Date of issue: 03.09.2025, 13:05

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com