

Kanlux

Kanlux MAH MAX

Kanlux MAH LED MAX is a hermetic fixture designed for demanding users. It is characterized by exceptional luminous efficacy: 160 lm/W. The Kanlux MAH LED MAX fixture is also easy, quick assembly (also thanks to quick connectors) and the possibility of connecting in lines. In Kanlux MAH LED MAX fixtures, we have used a grooved lampshade that increases the luminous flux. We emphasize the exceptional quality of this fixture with a 5-year warranty.

- 5 years Warranty under the terms of the warranty statement, available on our website
-



up to
160 $\frac{\text{lm}}{\text{W}}$

IP
66



 220-240 AC	 50	 ≥ 25000	 50000	 ≤ 6x MacAdam	 80	 SMD
		IP 66		 -20÷40		IK 08
	 1÷2.5	 0,5m				



MAH MAX 38W 12 CW RYF



MAH MAX 38W 12 CW RYF	38459	38	5800	6500	110	grey
MAH MAX 19W 06 NW RYF	38463	19	3050	4000	110	grey
MAH MAX 38W 12 NW RYF	38464	38	6080	4000	110	grey
MAH MAX 48W 15 NW RYF	38465	48	7680	4000	110	grey
MAH MAX 38W12NW RYF B	38469	38	6080	4000	110	black



MAH MAX 38W 12 CW RYF



MAH MAX 19W 06 NW RYF




MAH MAX 38W 12 NW RYF




MAH MAX 48W 15 NW RYF




MAH MAX 38W12NW RYF
B




MAH MAX 38W 12 CW RYF




MAH MAX 19W 06 NW RYF



MAH MAX 38W 12 NW RYF



MAH MAX 48W 15 NW RYF



MAH MAX 38W12NW RYF
B

Date of issue: 25.11.2025, 08:45

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN