

Kanlux

Kanlux LINCEA CCT

Kanlux LINCEA are modern linear ceiling luminaires with a rectangular structure, designed to illuminate large spaces. Thanks to their high luminous flux, reaching 5400 lm (for the 120 cm long version), they are perfect for corridors, passageways and educational rooms. Kanlux LINCEA luminaires allow you to adjust the power and colour of the light thanks to built-in switches. The user can easily select one of the three available powers (in each type of luminaire) and the colour temperature in the range of 3000K, 4000K and 6500K. Additionally, the LINCEA series equipped with a quick connector significantly facilitates and speeds up installation.

- 5 years Warranty under the terms of the warranty statement, available on our website



[V] 220-240 AC	[Hz] 50	≥20000	[h] 30000	ellipse ≤ 6x MacAdam	Ra 80	SMD
		IP 40		[°C] 5÷25	IK 08	
	[mm²] 0.5÷2.5	0---m 0,5m				



LINCEA 15-24W 07 CCT




LINCEA 15-24W 07 CCT	38795	15 / 24	max 2500 / 2550 / 2600	3000/4000/6500	140	white
LINCEA 30-45W 12 CCT	38796	30 / 45	max 4800 / 4900 / 5000	3000/4000/6500	140	white




LINCEA 15-24W 07 CCT



LINCEA 30-45W 12 CCT



LINCEA 15-24W 07 CCT



LINCEA 30-45W 12 CCT

LINCEA 15-24W 07 CCT			
	24 W	20 W	15 W
WW	2500lm	2200lm	1800lm
NW	2550lm	2250lm	1850lm
CW	2600lm	2300lm	1900lm

LINCEA 30-45W 07 CCT			
	45 W	38 W	30 W
WW	4800lm	4250lm	3500lm
NW	4900lm	4350lm	3550lm
CW	5000lm	4450lm	3600lm

Date of issue: 25.03.2025, 14:25

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

EN