

Kanlux

Kanlux LCOB 19W/M RGBW

- 3 years Warranty under the terms of the warranty statement, available on our website
- Proper controller Kanlux CTRL and Kanlux REMOTE are required for correct operation.





24V



LCOB 19W/M24IP00-RGBW

24 DC	1m = 5,3 (NW)		1m = max 420 (NW)	≤ 6x MacAdam	Ra 90	
	SMD	≥30000	30000		0,1m	5÷25
360°	0,5m = 21					



IP




LCOB 19W/M24IP00-RGBW	38913	0,5m = 2,65 (NW)	0,5m = 210 (NW)	RGB + 4000(W)	00	5000	G
LCOB 19W/M24IP65-RGBW	38914	0,5m = 2,65 (NW)	0,5m = 210 (NW)	RGB + 4000(W)	65	5000	G




LCOB 19W/M24IP00-
RGBW



LCOB 19W/M24IP65-
RGBW



LCOB 19W/M24IP00-
RGBW



LCOB 19W/M24IP65-
RGBW

Date of issue: 01.07.2025, 15:46

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com