

BLINGO AIO panels are a universal all-in-one solution that allows you to replace multiple LED panel variants with a single product, optimizing storage and enabling the use of the same model for different lighting power and color temperature preferences. Users can independently adjust both the color temperature (3000K, 4000K, 6500K) and the luminaire's power (32W/36W/40W) using switches, depending on the version. The panels are available in two sizes (60x60 cm and 120x30 cm), and the surface-mounted version comes with an integrated power supply. A color rendering index (CRI) of >90 and a luminous efficacy of up to 123 lm/W guarantee high-quality lighting parameters, while the versions with a microprismatic diffuser offer low glare (UGR>19). The panels are characterized by easy and quick installation (quick connectors are used), high durability (up to 50,000 hours) and are covered by a 5-year warranty.

- 5 years Warranty under the terms of the warranty statement, available on our website
- Panel/frame material: iron



















## BLINGO AIO SRM40W 60

			[W]	- <del>\\\</del> [Im]	<u>lm</u> W	Tc [K]			UGR
	BLINGO AIO SRM40W 60	39230	max 40	max 4900	max 123	3000/4000/6500	115	white	
	BLINGO UAIO SRM40W 60	39231	max 40	max 4370	max 109	3000/4000/6500	90	white	<19
	BLINGO AIO SRM40W120	39232	max 40	max 4900	max 123	3000/4000/6500	115	white	
	BLINGO UAIO SRM40W120	39233	max 40	max 4370	max 109	3000/4000/6500	90	white	<19



BLINGO AIO SRM40W 60




BLINGO UAIO SRM40W 60




BLINGO AIO SRM40W120




BLINGO UAIO SRM40W120




BLINGO AIO SRM40W 60



BLINGO UAIO SRM40W 60



BLINGO AIO SRM40W120



BLINGO UAIO SRM40W120

Photometry: the results obtained from testing were from a specific sample. Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

