






















# Kanlux


## Kanlux PRO-S S

Kanlux PRO-S is a series of modern street luminaires designed with efficiency, durability and ease of installation in mind. Luminous efficacy reaches 160 lm/W, and durability up to 100,000 hours. Durable aluminum alloy housing and IK09 tempered glass guarantee reliability in difficult conditions, and a high IP66 protection level ensures full resistance to dust and moisture. The luminaires allow for adjustment of the tilt angle, installation on Ø50–Ø62 mm poles and quick, tool-free access to the power supply chamber. Integrated SPD 10kV surge protection and programmable power supplies (also with the DALI option) ensure full functionality and safety. The luminaires are available in two sizes: S and M, which allows you to match the solution to specific installation needs. Kanlux PRO-S luminaires are covered by a 5-year manufacturer's warranty.

- 
- Protective glass material: Tempered glass



 220-240 AC	 50	 ≥30000	 100000	 Ra 70	 SMD	
		 66		 °C -20÷45	 08	
 0.4	 0.75-2.5					
						





PRO-S S 10W NW



PRO-S S 10W NW	<a href="#">39270</a>	10	grey	1580	X150/Y125	4000
PRO-S S 15W NW	<a href="#">39271</a>	15	grey	2440	X150/Y125	4000
PRO-S S 20W NW	<a href="#">39272</a>	20	grey	3270	X150/Y125	4000
PRO-S S 25W NW	<a href="#">39273</a>	25	grey	4100	X150/Y125	4000
PRO-S S 30W NW	<a href="#">39274</a>	30	grey	4770	X150/Y125	4000
PRO-S S 35W NW	<a href="#">39275</a>	35	grey	5600	X150/Y125	4000
PRO-S S 40W NW	<a href="#">39276</a>	40	grey	6200	X150/Y125	4000
PRO-S S 45W NW	<a href="#">39277</a>	45	grey	6950	X150/Y125	4000
PRO-S S 50W NW	<a href="#">39278</a>	50	grey	7750	X150/Y125	4000
PRO-S S 55W NW	<a href="#">39279</a>	55	grey	8230	X150/Y125	4000



PRO-S S 10W NW



PRO-S S 15W NW



PRO-S S 20W NW



PRO-S S 25W NW



PRO-S S 30W NW



PRO-S S 35W NW



PRO-S S 40W NW




PRO-S S 45W NW




PRO-S S 50W NW




PRO-S S 55W NW




PRO-S S 10W NW




PRO-S S 15W NW




PRO-S S 20W NW




PRO-S S 25W NW




PRO-S S 30W NW




PRO-S S 35W NW




PRO-S S 40W NW



PRO-S S 45W NW



PRO-S S 50W NW



PRO-S S 55W NW

Date of issue: 06.06.2025, 09:54

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)