

# Kanlux



## Kanlux PRO-S M

Kanlux PRO-S is a series of modern street luminaires designed with efficiency, durability and ease of installation in mind. Luminous efficacy reaches 160 lm/W, and durability up to 100,000 hours. Durable aluminum alloy housing and IK09 tempered glass guarantee reliability in difficult conditions, and a high IP66 protection level ensures full resistance to dust and moisture. The luminaires allow for adjustment of the tilt angle, installation on Ø50–Ø62 mm poles and quick, tool-free access to the power supply chamber. Integrated SPD 10kV surge protection and programmable power supplies (also with the DALI option) ensure full functionality and safety. The luminaires are available in two sizes: S and M, which allows you to match the solution to specific installation needs. Kanlux PRO-S luminaires are covered by a 5-year manufacturer's warranty.

- 5 years Warranty under the terms of the warranty statement, available on our website
- Protective glass material: Tempered glass



 [V] 220-240 AC	 [Hz] 50	 ≥30000	 [h] 100000	 ≤ 6x MacAdam	 Ra 70	 SMD
		 IP 66		 [°C] -20÷45	 IK 08	
 [m] 0.4	 [mm²] 0.75-2.5					





PRO-S M 70W NW



PRO-S M 70W NW	<a href="#">39280</a>	70	grey	11420	X150/Y125	4000
PRO-S M 75W NW	<a href="#">39281</a>	75	grey	12130	X150/Y125	4000
PRO-S M 80W NW	<a href="#">39282</a>	80	grey	12830	X150/Y125	4000
PRO-S M 85W NW	<a href="#">39283</a>	85	grey	13540	X150/Y125	4000
PRO-S M 90W NW	<a href="#">39284</a>	90	grey	14180	X150/Y125	4000
PRO-S M 95W NW	<a href="#">39285</a>	95	grey	14750	X150/Y125	4000
PRO-S M 100W NW	<a href="#">39286</a>	100	grey	15500	X150/Y125	4000
PRO-S M 105W NW	<a href="#">39287</a>	105	grey	16020	X150/Y125	4000
PRO-S M 110W NW	<a href="#">39288</a>	110	grey	16540	X150/Y125	4000



PRO-S M 70W NW



PRO-S M 75W NW



PRO-S M 80W NW



PRO-S M 85W NW



PRO-S M 90W NW



PRO-S M 95W NW




PRO-S M 100W NW




PRO-S M 105W NW




PRO-S M 110W NW




PRO-S M 70W NW




PRO-S M 75W NW




PRO-S M 80W NW




PRO-S M 85W NW




PRO-S M 90W NW




PRO-S M 95W NW



PRO-S M 100W NW



PRO-S M 105W NW



PRO-S M 110W NW

Date of issue: 06.06.2025, 09:45

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)