

# Kanlux



## Kanlux PRO-S Zhaga

Kanlux PRO-S is a series of modern street luminaires designed with efficiency, durability and ease of installation in mind. Luminous efficacy reaches 160 lm/W, and durability up to 100,000 hours. Durable aluminum alloy housing and IK09 tempered glass guarantee reliability in difficult conditions, and a high IP66 protection level ensures full resistance to dust and moisture. The luminaires allow for adjustment of the tilt angle, installation on Ø50–Ø62 mm poles and quick, tool-free access to the power supply chamber. Integrated SPD 10kV surge protection and programmable power supplies (also with the DALI option) ensure full functionality and safety. The luminaires are available in two sizes: S and M, which allows you to match the solution to specific installation needs. The PRO-S ZH version allows integration with ZHAGA control systems (optionally NEMA). Kanlux PRO-S luminaires are covered by a 5-year manufacturer's warranty.

- 5 years Warranty under the terms of the warranty statement, available on our website
- Protective glass material: Tempered glass



 [V] 220-240 AC	 [Hz] 50	 ≥30000	 [h] 100000	 ≤ 6x MacAdam	 Ra 70	 SMD
		<b>IP</b> 66		 [°C] -20÷45	<b>IK</b> 08	
 [m] 0.4	 [mm] 0.75-2.5		 Zhaga			





PRO-S S 10W-ZH NW



PRO-S S 10W-ZH NW	<a href="#">39289</a>	10	grey	1440	X150/Y125	4000
PRO-S S 15W-ZH NW	<a href="#">39290</a>	15	grey	2200	X150/Y125	4000
PRO-S S 20W-ZH NW	<a href="#">39291</a>	20	grey	3120	X150/Y125	4000
PRO-S S 25W-ZH NW	<a href="#">39292</a>	25	grey	3880	X150/Y125	4000
PRO-S S 30W-ZH NW	<a href="#">39293</a>	30	grey	4640	X150/Y125	4000
PRO-S S 35W-ZH NW	<a href="#">39294</a>	35	grey	5560	X150/Y125	4000
PRO-S S 40W-ZH NW	<a href="#">39295</a>	40	grey	6300	X150/Y125	4000
PRO-S S 45W-ZH NW	<a href="#">39296</a>	45	grey	7080	X150/Y125	4000
PRO-S S 50W-ZH NW	<a href="#">39297</a>	50	grey	7790	X150/Y125	4000
PRO-S S 55W-ZH NW	<a href="#">39298</a>	55	grey	8380	X150/Y125	4000
PRO-S S 60W-ZH NW	<a href="#">39299</a>	60	grey	9120	X150/Y125	4000
PRO-S S 65W-ZH NW	<a href="#">39300</a>	65	grey	9670	X150/Y125	4000



PRO-S S 10W-ZH NW



PRO-S S 15W-ZH NW



PRO-S S 20W-ZH NW



PRO-S S 25W-ZH NW



PRO-S S 30W-ZH NW



PRO-S S 35W-ZH NW



PRO-S S 40W-ZH NW



PRO-S S 45W-ZH NW



PRO-S S 50W-ZH NW




PRO-S S 55W-ZH NW




PRO-S S 60W-ZH NW




PRO-S S 65W-ZH NW




PRO-S S 10W-ZH NW




PRO-S S 15W-ZH NW




PRO-S S 20W-ZH NW




PRO-S S 25W-ZH NW




PRO-S S 30W-ZH NW




PRO-S S 35W-ZH NW




PRO-S S 40W-ZH NW




PRO-S S 45W-ZH NW




PRO-S S 50W-ZH NW



PRO-S S 55W-ZH NW



PRO-S S 60W-ZH NW



PRO-S S 65W-ZH NW

Date of issue: 06.06.2025, 10:06

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland [kanlux@kanlux.com](mailto:kanlux@kanlux.com)

EN