

Kanlux

Kanlux LCOB 14W/M 24 V



- 5 years Warranty under the terms of the warranty statement, available on our website



24V



 24 DC	 1m = 14	 III	 ≤ 6x MacAdam	 Ra 90	 Hg	
 COB	 ≥ 30000	 50000		 0,1m	 5÷25	 360° Φ _{use}



LCOB 14W/M 24 IP00-WW



IP



LCOB 14W/M 24 IP00-WW	39410	0,5m = 7	0,5m = 700	3000	00	5000	F
LCOB 14W/M 24 IP00-NW	39411	0,5m = 7	0,5m = 770	4000	00	5000	F
LCOB 14W/M 24 IP00-CW	39412	0,5m = 7	0,5m = 770	6500	00	5000	F
LCOB 14W/M 24 IP65-WW	39413	0,5m = 7	0,5m = 700	3000	65	5000	F
LCOB 14W/M 24 IP65-NW	39414	0,5m = 7	0,5m = 770	4000	65	5000	F
LCOB 14W/M 24 IP65-CW	39415	0,5m = 7	0,5m = 770	6500	65	5000	F



LCOB 14W/M 24 IP00-WW



LCOB 14W/M 24 IP00-NW



LCOB 14W/M 24 IP00-CW




LCOB 14W/M 24 IP65-WW




LCOB 14W/M 24 IP65-NW



LCOB 14W/M 24 IP65-CW



LCOB 14W/M 24 IP00



LCOB 14W/M 24 IP65

Accessories

39530 CON P 10 LED band connector, CON P 10 (39530)



39531 CON P 10 CP LED band connector, CON P 10 CP (39531)



39532 CON P 10 CPC LED band connector, CON P 10 CPC (39532)



39533 CON P 10 L LED band connector, CON P 10 L (39533)



Date of issue: 01.10.2025, 17:23
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.
Kanalux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com