


Kanlux

Kanlux ARBOREA LED natynkowy



[V] 220-240 AC	[Hz] 50	≥ 30000	50000	$Ra \leq 6x$ MacAdam	SMD
		IP 20		$5 \div 25$	
$1.5 \div 2.5$		$0.5m$	CE	EAC	UK CA



AR-M-MPR-GW-NT



AR-ML-NW-MPR-GW-NT	39451	23	4450	4000	X75/Y90	złote drewno
AR-ML-WW-MPR-GW-NT	39454	23	4270	3000	X75/Y90	złote drewno
AR-ML-NW-MPR-BRW-NT	39457	23	4450	4000	X75/Y90	brązowe drewno
AR-ML-WW-MPR-BRW-NT	39460	23	4270	3000	X75/Y90	brązowe drewno
AR-ML-NW-MAT-GW-NT	39463	23	4450	4000	X85/Y95	złote drewno
AR-ML-WW-MAT-GW-NT	39466	23	4270	3000	X85/Y95	złote drewno
AR-ML-NW-MAT-BRW-NT	39469	23	4450	4000	X85/Y95	brązowe drewno
AR-ML-WW-MAT-BRW-NT	39472	23	4270	3000	X85/Y95	brązowe drewno
AR-ML-NW-5D-GW-NT	39475	24	4250	4000	X60/Y60	złote drewno
AR-ML-WW-5D-GW-NT	39478	24	4060	3000	X60/Y60	złote drewno
AR-ML-NW-5D-BRW-NT	39481	24	4250	4000	X60/Y60	brązowe drewno
AR-ML-WW-5D-BRW-NT	39484	24	4060	3000	X60/Y60	brązowe drewno
AR-ML-NW-S5D-GW-NT	39487	24	3960	4000	X60/Y60	złote drewno
AR-ML-WW-S5D-GW-NT	39490	24	4150	3000	X60/Y60	złote drewno
AR-ML-NW-S5D-BRW-NT	39493	24	3960	4000	X60/Y60	brązowe drewno
AR-ML-WW-S5D-BRW-NT	39496	24	4150	3000	X60/Y60	brązowe drewno



AR-M-MPR-GW-NT



AR-M-MPR-BRW-NT



AR-M-MAT-GW-NT



AR-M-MAT-BRW-NT



AR-M-5D-GW-NT




AR-M-5D-BRW-NT




AR-M-S5D-GW-NT




AR-M-S5D-BRW-NT




AR-M-MPR-NT



AR-M-MAT-NT



AR-M-5D-NT



AR-M-S5D-NT

Accessories

32541

ALIN CORD 1F-B

Power supply terminal for ALIN luminaires and tracks, 1-phase, black, 150 cm



32535

ALIN CORD SQ 1F-B



07871

ROPE-NT 150 SINGLE

ROPE-NT 150 SINGLE steel rope (single) for suspending fittings, 2 pcs. in a set



Date of issue: 27.11.2025, 09:13

We reserve the right to make technical changes. The data contained in this material are not legally binding.

Photometry: the results obtained from testing were from a specific sample.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com