

## Residual-current circuit breaker, 2P



KRD10-2/16/30-F

[Hz] 50	°C -25÷40	IP 20	2P	2	TH 35	Ui [V] 400
(mm <sup>2</sup> ) max 25	CE	EAC	VDE	UK CA	⚡	

	[V]	In [A]	IΔn [mA]	Residual-current protection type	
KRD10-2/16/30-F	45769	230 AC 16	30	F	2
KRD10-2/25/30-F	45770	230 AC 25	30	F	2
KRD10-2/40/30-F	45771	230 AC 40	30	F	2
KRD10-2/25/100-F	45772	230 AC 25	100	F	2
KRD10-2/40/100-F	45773	230 AC 40	100	F	2
KRD10-2/25/300-F	45774	230 AC 25	300	F	2
KRD10-2/40/300-F	45775	230 AC 40	300	F	2

## Residual-current circuit breaker, 2P



KRD10-2/16/30-F



KRD10-2/25/30-F



KRD10-2/40/30-F



KRD10-2/25/100-F




KRD10-2/40/100-F




KRD10-2/25/300-F




KRD10-2/40/300-F




KRD10-2/16/30-F



KRD10-2/25/30-F




KRD10-2/40/30-F




KRD10-2/25/100-F


## Residual-current circuit breaker, 2P



KRD10-2/40/100-F



KRD10-2/25/300-F



KRD10-2/40/300-F