

KRO

Residual-current circuit breaker with overcurrent module, 6kA, 2P



[V] 230 AC	[Hz] 50	°C -25÷40	IP 20	Icn [A] 6000	1	2P
2	TH 35	Ui [V] 400	(mm²) max 25	CE	UK CA	

KRO6-1M-2/B6/30-A

		In [A]	IΔn [mA]	Residual-current protection type
KRO6-1M-2/B6/30-A	90405	B 6	30	A
KRO6-1M-2/B10/30-A	90406	B 10	30	A
KRO6-1M-2/B13/30-A	90407	B 13	30	A
KRO6-1M-2/B16/30-A	90408	B 16	30	A
KRO6-1M-2/B20/30-A	90409	B 20	30	A
KRO6-1M-2/B25/30-A	90410	B 25	30	A
KRO6-1M-2/B32/30-A	90411	B 32	30	A
KRO6-1M-2/C6/30-A	90412	C 6	30	A
KRO6-1M-2/C10/30-A	90413	C 10	30	A
KRO6-1M-2/C13/30-A	90414	C 13	30	A
KRO6-1M-2/C16/30-A	90415	C 16	30	A
KRO6-1M-2/C20/30-A	90416	C 20	30	A
KRO6-1M-2/C25/30-A	90417	C 25	30	A
KRO6-1M-2/C32/30-A	90418	C 32	30	A

KRO

Residual-current circuit breaker with overcurrent module, 6kA, 2P



KRO6-1M-2/B6/30-A



KRO6-1M-2/B10/30-A



KRO6-1M-2/B13/30-A



KRO6-1M-2/B16/30-A



KRO6-1M-2/B20/30-A



KRO6-1M-2/B25/30-A



KRO6-1M-2/B32/30-A



KRO6-1M-2/C6/30-A



KRO6-1M-2/C10/30-A



KRO6-1M-2/C13/30-A



KRO6-1M-2/C16/30-A



KRO6-1M-2/C20/30-A

KRO

Residual-current circuit breaker with overcurrent module, 6kA, 2P



KRO6-1M-2/C25/30-A



KRO6-1M-2/C32/30-A

